



Product Specification

Sodium Thiocyanate

Chemical Name:	Sodium thiocyanate
Molecular Formula:	NaSCN
Molecular Mass:	81,1 g/mol
CAS-No.:	540-72-7
EC-No.:	615-004-00-3

Properties

Bulk density:	approx. 750 kg/m ³
Solubility in water (20°C):	approx. 1250 g/l
Melting point:	approx. 310 °C

Specification

Appearance:	white crystals
Content (on dried basis):	min. 99,0 %
Moisture:	max. 3,0 %
Iron:	max. 2 mg/kg
Iodine value:	max. 20 mg I ₂ /100 g
pH (5% aqueous solution):	5,0 – 9,0
Sulphides:	max. 15 mg/kg
Ammonia (as NH ₃):	max. 200 mg/kg

Typical Characteristics

Chloride:	< 100 mg/kg
Sulphate:	< 200 mg/kg
Nitrate:	< 50 mg/kg
Heavy metals:	< 5 mg/kg
Content (on dried basis):	> 99,8 %

Analytical methods are available on request.

Major Applications

- In the fiber industry in spinning baths for acrylic fibers.
- In the water treatment industry as corrosion inhibitor.
- In the textile industry as adjuvant.
- In agriculture as an intermediate in the manufacture of herbicides.
- In the photographic industry as sensitizer and stabilizer.
- In metal plating as a brightener for copper baths.
- In concrete industry as an accelerator.

Storage

Store in a cool and dry place. The product is very hygroscopic. Avoid contact with acids. Upon contact with materials containing iron a red colour is obtained. It is advised to re-test the material after three years of storage.

Packing and Transport

Sodium thiocyanate is delivered in:	25 kg net in paper bags (SAP-No. 5404306)
Hazard Identification No.:	none
UN-No.:	none

Safety advice

For transport, handling and first aid instructions we refer to our Material Safety Data Sheet (MSDS).

The information presented herein is true and accurate to the best of our knowledge, but without any guarantee unless explicitly given. Since the conditions of use are beyond our control we disclaim any liability including for patent infringement, incurred in connection with the use of this product, data and suggestions.